(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization International Bureau



. | 1841 | 1844 | 1854 | 1864 | 1864 | 1864 | 1864 | 1864 | 1864 | 1864 | 1864 | 1864 | 1864 | 1864 | 1864 | 1

(43) International Publication Date 17 July 2003 (17.07.2003)

PCT

(10) International Publication Number WO 03/059030 A1

(51) International Patent Classification7:

. .

(21) International Application Number: PCT/FI03/00003

(22) International Filing Date: 3 January 2003 (03.01.2003)

(25) Filing Language:

Finnish

H05K 9/00

(26) Publication Language:

English

(30) Priority Data: 20020025

8 January 2002 (08.01.2002) FI

(71) Applicant (for all designated States except US): 4-D NEUROIMAGING OY [FI/FI]; P.O. Box 68, FIN-00511 Helsinki (FI).

(72) Inventor; and

(75) Inventor/Applicant (for US only): SIMOLA, Juha [FI/FI]; c/o 4-D Neuroimaging Oy, P.O. Box 68, FIN-00511 Helsinki (FI).

(74) Agent: PAPULA OY; P.O. Box 981 (Fredrikinkatu 61 A), FIN-00101 Helsinki (FI).

(81) Designated States (national): AE, AG, AL, AM, AT (utility model), AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ (utility model), CZ, DE (utility model), DE, DK (utility model), DK, DM, DZ, EC, EE (utility model), EE, ES, FI (utility model), FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK (utility model), SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: WALL ELEMENT FOR MAGNETICALLY SHIELDED ROOM AND MAGNETICALLY SHIELDED ROOM



(57) Abstract: The invention relates to a wall element for a magnetically shielded room and to a magnetically shielded room. The wall element comprises at least one first layer (1) which is formed of metal plate having a high electrical conductivity, and at least two layers, a second layer (2) and a third layer (3), which consist of metal plates having a high magnetic permeability. The layers (1,2,3) are superimposed one on top of another in surface contact with each other without any separating air gaps, so that each first layer (1) having a high electrical conductivity lies between each second (2) and third layers (3) having a high permeability substantially in surface contact with the second and third layers, the layers together forming a compact structure in which the product $(\sigma \times \mu)$ of electrical conductivity (σ) and

permeability (µ) is maximized so as to minimize the penetration depth of magnetic interference.

WO 03/059030 A1